

Grease & Oil Remover

General Purpose Carpet Cleaner for Sticky and Oily Substances

MANUFACTURER: XL North, P.O. Box 2682, 63 Water Street, Fall River, MA 02722

Telephone: 888-530-2259 Fax: 508-673-2222

SECTION I - IDENTIFICATION

PRODUCT NAME: Grease & Oil Remover PRODUCT TYPE: General Purpose Carpet Cleaner

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENTS:

Hazardous Ingredient CAS Number PEL

SECTION III - PHYSICAL AND CHEMICAL DATA

BOILING POINT212 °F SPECIFIC GRAVITY......1.01 VAPOR PRESSURESame as water PERCENT SOLIDS......15% - 20% VAPOR DENSITY (AIR=1)Same as water EVAPORATION RATE (WATER=1)Same as water SOLUBILITY IN WATERSoluble APPEARANCE AND ODORClear liquid, little odor

OTHERpH (7.5), VOC Content: 300 grams/Liter

SECTION IV - FIRE AND EXPLOSION DATA FLASH POINT.....> 212 °F

METHOD USEDASTM D-93

FLAMMABLE LIMITS IN AIR (% BY VOLUME) LOWER.....Non-flammable UPPER.....Non-flammable EXTINGUISHING MEDIAWater, dry chemical, CO2 AUTO-IGNITION TEMPERATURENot determined

SECTION V - PHYSICAL HAZARDS

STABILITY..... .Stable INCOMPATIBLE MATERIALS.....None known HAZARDOUS DECOMPOSITION PRODUCTS..None known HAZARDOUS POLYMERIZATIONWill not occur CONDITIONS TO AVOID......None known

UNUSUAL FIRE AND EXPLOSION HAZARDS.. None known

SECTION VI - HEALTH HAZARDS

(SIGNS AND SYMPTOMS OF EXPOSURE: SEE SECTION 2)

CHRONIC OVEREXPOSURENone known

THRESHOLD LIMIT VALUENot determined ACUTE OVEREXPOSURE EYE CONTACT:Avoid eye contact. Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. INHALATION:Breathing of vapor may cause irritation of nose SKIN CONTACT:Avoid skin contact. Can cause skin irritation. Symptoms may include redness and burning of skin, or rash. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea). SECTION VI - (CONT'D)

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE......None known LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN BY:

OSHANo

SECTION VII - FIRST AID

INHALATION: In case of overexposure move victim to fresh air. If breathing difficult, give oxygen. Get medical attention.

least 15 minutes. Seek medical attention if irritation persists.

SKIN CONTACT:In case of contact wash skin with soap and water.

attention immediately.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:.....Store at 40 - 110 °F as recommendation. Provide adequate ventilation in the workplace. STEPS TO BE TAKEN IF MATERIAL IS

RELEASED OR SPILLED:.....Cover small spills using inert absorbent, then sweep up and place in a waste disposal container.

WASTE DISPOSAL METHODS:Dispose of in accordance with Federal RCRA and applicable State and Local regulations.

Section IX - Special Precautions and Spill/Leak Protection

RESPIRATORY PROTECTION:.....None required with adequate ventilation. VENTILATION:General mechanical. GLOVES:Impervious. Neoprene rubber recommended. EYE PROTECTION:Safety glasses or splashproof goggles. OTHER:Keep containers closed and properly stored. Maintain an eyewash facility in the work area.

SECTION X - OTHER REGULATORY INFORMATION

NEPA HEALTH: 1 NFPA FLAMMABILITY: 1 NFPA REACTIVITY: 0

SECTION XI - PRECAUTIONARY STATEMENTS

WARNING: The information contained in this MSDS is based on the data available to us from sources we believe to be reliable. No warranty or guaranty expressed or implied is made regarding the accuracy of this data or the results obtained from the reliance on this data. The manufacturer assumes no responsibility for injury from the use of this product. Be safe- read this product safety information and pass it on to all persons who may be exposed to this product. Federal law requires it.



Questions or Comments: 888-530-2259

www.xlnorth.com

©2013 XL North, Fall River, MA 02722 USA

FOR CHEMICAL EMERGENCY

Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night

Within USA and Canada: 1 800-424-9300 Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

Rev. 021313a