

Green Floor Stripper

Environmentally Friendly Product



Tech Data Sheet

XL Green Floor Stripper is an EPA DFE approved stripper for top scrubbing through heavy stripping. A stripper that easily cuts through multi-layers of burnished floor finish. Low foaming, no scrub and no rinse features make this product a must for all professional floor care systems

Where To Use: XL Green Floor Stripper is formulated for the rapid removal of all floor finishes from resilient flooring including: vinyl, vinyl asbestos, vinyl composition, asphalt tiles. Also ideal for finished non-resilient such as: terrazzo, marble, ceramic, quarry tile, concrete, and poured epoxy flooring.

How To Use: Mop/Wet Vacuum: Apply liberally with a mop to an area small enough so as not to allow the product to dry and allow standing for 5 to 10 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply XL Green Floor Finish for desired look.

TECHNICAL SPECIFICATIONS

COLOR: Clear TYPE: Liquefying Stripper FORM: Liquid SOLID CONTENT: N/A SCENT: Odorless INITIAL GLOSS: N/A PH: 11.5 RECOAT DRYING TIME: N/A FLASH POINT: 120 degrees F FOAM: N/A VISCOSITY: Water Thin SLIP COEFFICIENT: N/A STORAGE (Unopened): 1 year minimum REMOVABILITY: N/A BIODEGRADABLE: N/A WEIGHT/GAL: N/A SCUFF RESISTANCE: N/A WEIGHT/GAL: N/A SHIPPING CLASS: Corrosive Liquid HIGH SPEED BURNISH: N/A PACKAGING: 4x1 Gal. Cases DILUTION: 1:4					
SCENT: Odorless INITIAL GLOSS: N/A pH: 11.5 RECOAT DRYING TIME: N/A FLASH POINT: 120 degrees F COVERAGE: N/A FOAM: N/A LEVELING: N/A VISCOSITY: Water Thin SLIP COEFFICIENT: N/A STORAGE (Unopened): 1 year minimum REMOVABILITY: N/A BIODEGRADABLE: N/A SCUFF RESISTANCE: N/A WEIGHT/GAL: N/A DETERGENT RESISTANT: N/A SHIPPING CLASS: Corrosive Liquid HIGH SPEED BURNISH: N/A	COLOR:	Clear	TYPE:	Liquefying Stripper	
pH: 11.5 RECOAT DRYING TIME: N/A FLASH POINT: 120 degrees F COVERAGE: N/A FOAM: N/A LEVELING: N/A VISCOSITY: Water Thin SLIP COEFFICIENT: N/A STORAGE (Unopened): 1 year minimum REMOVABILITY: N/A BIODEGRADABLE: N/A SCUFF RESISTANCE: N/A WEIGHT/GAL: N/A DETERGENT RESISTANT: N/A SHIPPING CLASS: Corrosive Liquid HIGH SPEED BURNISH: N/A	FORM:	Liquid	SOLID CONTENT:	.N/A	
FLASH POINT: 120 degrees F COVERAGE: N/A FOAM: N/A LEVELING: N/A VISCOSITY: Water Thin SLIP COEFFICIENT: N/A STORAGE (Unopened): 1 year minimum REMOVABILITY: N/A BIODEGRADABLE: N/A SCUFF RESISTANCE: N/A WEIGHT/GAL: N/A DETERGENT RESISTANT: N/A SHIPPING CLASS: Corrosive Liquid HIGH SPEED BURNISH: N/A	SCENT:	Odorless	INITIAL GLOSS:	.N/A	
FOAM: N/A LEVELING: N/A VISCOSITY: Water Thin SLIP COEFFICIENT: N/A STORAGE (Unopened): 1 year minimum REMOVABILITY: N/A BIODEGRADABLE: N/A SCUFF RESISTANCE: N/A WEIGHT/GAL: N/A DETERGENT RESISTANT: N/A SHIPPING CLASS: Corrosive Liquid HIGH SPEED BURNISH: N/A	pH:	11.5	RECOAT DRYING TIME:	N/A	
VISCOSITY: Water Thin SLIP COEFFICIENT: N/A STORAGE (Unopened): 1 year minimum REMOVABILITY: N/A BIODEGRADABLE: N/A SCUFF RESISTANCE: N/A WEIGHT/GAL: N/A DETERGENT RESISTANT: N/A SHIPPING CLASS: Corrosive Liquid HIGH SPEED BURNISH: N/A	FLASH POINT:	120 degrees F	COVERAGE:	.N/A	
STORAGE (Unopened): 1 year minimum REMOVABILITY:	FOAM:	N/A	LEVELING:	. N/A	
BIODEGRADABLE:	VISCOSITY:	Water Thin	SLIP COEFFICIENT:	.N/A	
WEIGHT/GAL:	STORAGE (Unopened):	1 year minimum	REMOVABILITY:	.N/A	
SHIPPING CLASS: Corrosive Liquid HIGH SPEED BURNISH:N/A	BIODEGRADABLE:	N/A	SCUFF RESISTANCE:	.N/A	
· · · · · · · · · · · · · · · · · · ·	WEIGHT/GAL:	N/A	DETERGENT RESISTANT: .	.N/A	
PACKAGING:4x1 Gal. Cases DILUTION:1:4	SHIPPING CLASS:	Corrosive Liquid	HIGH SPEED BURNISH:	N/A	
	PACKAGING:	4x1 Gal. Cases	DILUTION:	. 1:4	

©2014 XL North, Fall River, MA 02722 USA

Questions or Comments:

FOR COMMERCIAL AND INDUSTRIAL USE ONLY

888-530-2259



U.S. EPA **Recognized for Safer Chemistry** www.epa.gov/dfe