



SPECIFICATIONS (50cm x 50cm Modular with Underscore™ ES cushion):

Specifications subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results available upon request.

- P/6721 Links
- P/6722 Median
- P/6723 Mesh
- P/6724 Random

Construction	Tufted, Textured Loop Pile
Face Fiber	100% Milliken Certified WearOn® Type 6,6 Nylon
Stain Repel/Stain Resist/Soil Release	StainSmart®
Antimicrobial	AlphaSan® Built-In Protection
Dye Method	Millitron®
Gauge	1/10 (39.4/10 cm.)
Rows	14.4/in. (56.7/10 cm.)
Tufts	143.9/sq.in. (2,230.3/100 sq.cm.)
Average Density (oz./cubic yd.)	4,642.6
Standard Backing	PVC-Free Underscore™ ES cushion
	Available with TractionBack®
Nominal Total Thickness	0.295 in. (7.49 mm.)
Tile Size	50cm x 50cm (19.7 x 19.7 in.)
Nominal Total Weight	89.0 oz./sq.yd. (3,017.8 g./sq.m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 hrs.
Crocking (AATCC 165)	≥ 4.0 wet or dry
Static Electricity (AATCC-134) 20% R.H.,70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Dimensional Stability - Aachener Test (DIN Standard 54318)	≤ 0.2%
Appearance Retention Rating (CRI TM101)	Severe Use
Indoor Air Quality – CRI Green Label Plus™	GLP0793, Carpet Category 5Y

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Milliken modular carpet is PVC free and produced with alternative energy. It is certified to the industry’s single green carpet standard and contains up to 35% recycled content. Milliken is the only carpet manufacturer with certified carbon negative status, zero waste to landfill, Cleaner and Greener™/Health & Climate Care certification and our No Carpet to Landfill pledge. No other carpet contributes more toward LEED®.



This modular carpet with ES backing has been certified as an Environmentally Preferable Product, SCS Sustainable Choice Gold.

Applicable Milliken Warranties include:

- | | |
|---|---|
| Lifetime Antimicrobial Protection (AlphaSan®) | Lifetime Face Fiber Wear |
| Lifetime Antistatic | Lifetime Floor Compatibility |
| Lifetime Color Pattern Permanency | Lifetime Floor Release |
| Lifetime Cushion Resiliency | Lifetime Moisture Resistance |
| Lifetime Delamination of Backing | Lifetime Staining/Soiling (StainSmart®) |
| Lifetime Dimensional Stability | Lifetime Tuft Bind |
| Lifetime Edge Ravel | Flammability |