

Starnet High Performance LVT Product Specifications

Starnet High Performance LVT shall be constructed with a .020" high density wearlayer. All products shall have an overall gauge of .100" (2.5 mm) nominal. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 10-year Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, CENTI 6000 SP, or Schönox® Roll & Go™ Installation shall be in accordance with the latest installation guidelines for Starnet High Performance LVT.

Starnet High Performance LVT

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Layered tile consisting of wearlayer, decorative film, and backing with pre- and post-consumer content		
Overall Thickness:	.100" / 2.5 mm (nominal)		
Wearlayer Thickness:	.020" / .5 mm clear, rigid high density PVC		
Size:	Planks 6" x 36", Tiles 18" x 18" & 12" x 18"		
Weight:	.75 lb/sq. ft. (33.75 lbs./45 sf ctn)		
Packaging:	45 sf/ctn		
Edge Treatment:	Square		
Surface Texture:	Standard as shown in sample folder		
Warranty:	10 years Commercial		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class1 CRF>0.45
	ASTM E 662	Smoke Density	Passes
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		All ADA compliant	
		FTC Slip Resistant Classified Product	