



# XL UF

## GLOSS FLOOR FINISH

Urethane Fortified Formula

Non-Slip Fast Drying  
Premium Floor Finish

INFUSED WITH  
**INTERSEPT®**  
ANTIMICROBIAL

### Tech Data Sheet



As a highly versatile extended-wear floor sealer/finish, **XL UF Urethane Fortified Floor Finish** provides durable protection without creating unwanted build-up. It is formulated with exclusive micro-molecular technology that allows easy maintenance and exceptional film clarity.

#### WHERE TO USE

**XL UF Urethane Fortified Floor Finish** offers a variety of surface applications including VCT, Terrazzo, Asbestos Tile, Asphalt Tile, Concrete, Sealed Wood and other resilient floors. Non-resilient floors such as Marble may require testing for adhesion.

#### DIRECTIONS

**PREPARATION:** Seal off areas to be stripped or finished. Floors may be very slippery until dry. Prior to application, floors should be completely stripped of old finish and neutralized. Floors should be completely dry before applying first coat and all subsequent coats. Do not use an air mover or fan to dry finish.

#### INTERSEPT® ANTIMICROBIAL

**Intersept®** is an antimicrobial preservative that protects the cured floor finish against a broad spectrum of bacteria and fungi, including odor - and stain-causing microorganisms.

**Intersept®** is registered with the EPA and meets stringent certification standards set by the three most recognized testing protocols related to indoor environmental quality – the State of Washington Protocol, CRI Green Label and GSA Antimicrobial Certification. Yet, despite its proven ability as a microbial inhibiting preservative, **Intersept®** is low in toxicity and contains no arsenic, heavy metals, phenols or formaldehyde.

#### TECHNICAL SPECIFICATIONS

COLOR: ..... Milk-White  
 FORM: ..... Liquid  
 SCENT: ..... Mild Solvent/Polymer  
 pH: ..... 8.0 - 9.0  
 FLASH POINT: ..... None  
 FOAM: ..... None  
 VISCOSITY: ..... Water Thin  
 STORAGE (Unopened): ..... 1 Year @ R.T.  
 BIODEGRADABLE: ..... Yes  
 WEIGHT/GAL: ..... 8.5  
 SHIPPING CLASS: ..... None  
 PACKAGING: ..... 1 Gal., 5 Gal.

TYPE: ..... Urethane/Acrylic Polymer  
 SOLID CONTENT: ..... 21%  
 INITIAL GLOSS: ..... High  
 RECOAT DRYING TIME: ..... Minimum 30 Minutes  
 COVERAGE: ..... 2500 - 3000 sq. ft.  
 LEVELING: ..... Excellent  
 SLIP COEFFICIENT: ..... 0.57  
 REMOVABILITY: ..... Excellent  
 SCUFF RESISTANCE: ..... Very Good  
 DETERGENT RESISTANT: .. Very Good  
 HIGH SPEED BURNISH: ..... Yes  
 DILUTION: ..... Use As Is

Leading floor finish  
without protection



Aspergillus  
Mold

**XL ANTIMICROBIAL  
PROTECTED  
FLOOR FINISH**  
with *Intersept®*

FOR COMMERCIAL AND INDUSTRIAL USE ONLY

©2012 XL North, Fall River, MA 02722 USA

Questions or Comments:  
**888-530-2259**

[www.xlnorth.com](http://www.xlnorth.com)

Another Great  
Product By



Rev. 110111a