Date: 07/20/09 Supersedes: 05/19/09



P/6721 Links

Construction Tufted, Textured Loop Pile

Face Fiber 100% Milliken-Certified WearOn® Type 6,6 Nylon

Stain Repel / Stain Resist / Soil Release StainSmart®

Antimicrobial AlphaSan® Built-In Protection

Dye Method Millitron®

Gauge 1/10 (39.4/10 cm.) **Rows** 14.4/in. (56.7/10 cm.)

Tufts 144.0/sq.in. (2,234.0/100 sq.cm.)

Density Factor 197,121

Standard Backing PVC-Free Underscore™ ES cushion

Available with TractionBack®

Recycled Content by Total Product Weight 28% Pre-Consumer, 4% Post-Consumer

Nominal Total Thickness 0.27 in. (6.9 mm.)

Tile Size 50cm x 50cm (19.7 x 19.7 in.)

Nominal Total Weight 89.0 oz./sq.yd. (3,017.8 g./sq.m.)

Flammability (Radiant Panel ASTM-E-648) ≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or ASTM-E-662) ≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859) Self-Extinguishing

Lightfastness (AATCC 16E) \geq 4.0 at 80 hrs. Crocking (AATCC 165) \geq 4.0 wet or dry

Static Electricity (AATCC-134) 20% R.H.,70° F. ≤ 3.5 KV, Permanent Conductive Fiber

Dimensional Stability - Aachener Test (DIN Std 54318) ≤ 0.2%

Appearance Retention Rating (CRI TM101) Severe Use

Recommended Maintenance MilliCare® Textile and Carpet Care Service Network

Indoor Air Quality – CRI Green Label Plus™ GLP0793, Carpet Category 5Y

Design Copyright - Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.







Recommended Installation Method: Monolithic



Warranties:

Lifetime Antimicrobial Protection (AlphaSan®) Lifetime Antistatic Lifetime Color Pattern Permanency Lifetime Cushion Resiliency Lifetime Delamination of Backing

Lifetime Dimensional Stability

Lifetime Edge Ravel

Lifetime Face Fiber Wear Lifetime Floor Compatibility Lifetime Floor Release Lifetime Moisture Resistance Lifetime Staining/Soiling (StainSmart®) Lifetime Tuft Bind Flammability



