



**P/6722 Median**

<b>Construction</b>	Tufted, Textured Loop Pile
<b>Face Fiber</b>	100% Milliken-Certified WearOn® Type 6,6 Nylon
<b>Stain Repel / Stain Resist / Soil Release</b>	StainSmart®
<b>Antimicrobial</b>	AlphaSan® Built-In Protection
<b>Dye Method</b>	Millitron®
<b>Gauge</b>	1/10 (39.4/10 cm.)
<b>Rows</b>	14.4/in. (56.7/10 cm.)
<b>Tufts</b>	144.0/sq.in. (2,234.0/100 sq.cm.)
<b>Density Factor</b>	197,121
<b>Standard Backing</b>	PVC-Free Underscore™ ES cushion Available with TractionBack®
<b>Recycled Content by Total Product Weight</b>	28% Pre-Consumer, 4% Post-Consumer
<b>Nominal Total Thickness</b>	0.27 in. (6.9 mm.)
<b>Tile Size</b>	50cm x 50cm (19.7 x 19.7 in.)
<b>Nominal Total Weight</b>	89.0 oz./sq.yd. (3,017.8 g./sq.m.)
<b>Flammability (Radiant Panel ASTM-E-648)</b>	≥ 0.45 (Class I)
<b>Smoke Density (NFPA-258-T or ASTM-E-662)</b>	≤ 450
<b>Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)</b>	Self-Extinguishing
<b>Lightfastness (AATCC 16E)</b>	≥ 4.0 at 80 hrs.
<b>Crocking (AATCC 165)</b>	≥ 4.0 wet or dry
<b>Static Electricity (AATCC-134) 20% R.H., 70° F.</b>	≤ 3.5 KV, Permanent Conductive Fiber
<b>Dimensional Stability - Aachener Test (DIN Std 54318)</b>	≤ 0.2%
<b>Appearance Retention Rating (CRI TM101)</b>	Severe Use
<b>Recommended Maintenance</b>	MilliCare® Textile and Carpet Care Service Network
<b>Indoor Air Quality – CRI Green Label Plus™</b>	GLP0793, Carpet Category 5Y

Design Copyright – Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



Recommended Installation Method: Monolithic



**Warranties:**

- Lifetime Antimicrobial Protection (AlphaSan®)
- Lifetime Antistatic
- Lifetime Color Pattern Permanency
- Lifetime Cushion Resiliency
- Lifetime Delamination of Backing
- Lifetime Dimensional Stability
- Lifetime Edge Ravel

- Lifetime Face Fiber Wear
- Lifetime Floor Compatibility
- Lifetime Floor Release
- Lifetime Moisture Resistance
- Lifetime Staining/Soiling (StainSmart®)
- Lifetime Tuft Bind
- Flammability

