



P/6723 Mesh

Construction	Tufted, Textured Loop Pile
Face Fiber	100% Milliken-Certified WearOn® Type 6,6 Nylon
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® Built-In Protection
Dye Method	Millitron®
Gauge	1/10 (39.4/10 cm.)
Rows	14.4/in. (56.7/10 cm.)
Tufts	144.0/sq.in. (2,234.0/100 sq.cm.)
Density Factor	197,121
Standard Backing	PVC-Free Underscore™ ES cushion Available with TractionBack®
Recycled Content by Total Product Weight	28% Pre-Consumer, 4% Post-Consumer
Nominal Total Thickness	0.27 in. (6.9 mm.)
Tile Size	50cm x 50cm (19.7 x 19.7 in.)
Nominal Total Weight	89.0 oz./sq.yd. (3,017.8 g./sq.m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 hrs.
Crocking (AATCC 165)	≥ 4.0 wet or dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Dimensional Stability - Aachener Test (DIN Std 54318)	≤ 0.2%
Appearance Retention Rating (CRI TM101)	Severe Use
Recommended Maintenance	MilliCare® Textile and Carpet Care Service Network
Indoor Air Quality – CRI Green Label Plus™	GLP0793, Carpet Category 5Y

Design Copyright – Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



Recommended Installation Method: Monolithic



Warranties:

- Lifetime Antimicrobial Protection (AlphaSan®)
- Lifetime Antistatic
- Lifetime Color Pattern Permanency
- Lifetime Cushion Resiliency
- Lifetime Delamination of Backing
- Lifetime Dimensional Stability
- Lifetime Edge Ravel

- Lifetime Face Fiber Wear
- Lifetime Floor Compatibility
- Lifetime Floor Release
- Lifetime Moisture Resistance
- Lifetime Staining/Soiling (StainSmart®)
- Lifetime Tuft Bind
- Flammability

