



Starnet High Performance LVT by Centiva



Product Features and Benefits

High Performance LVT

Environmental Features and Benefits

Contains 32% Post Industrial Content
Contains 3% Post Consumer Content
100% Recyclable
Low VOCs – FloorScore and GREENGUARD Certified
Can be reclaimed at the end of its life cycle



High Performance LVT

Product Range

Collection of 37 products in an 'easy to present folder'
20 planks available in 6" x 36"
17 tiles available in 18" x 18" & 12" x 18"

Standard surfaces chosen to complement product
Standard square edge







Product Specifications

High Performance LVT

Classification: ASTM 1700 Class III Solid Vinyl Tile

Construction: Layered tile consisting of wearlayer,

decorative film, and backing

Overall Thickness: 0.100"/2.5 mm (nominal)

Wearlayer Thickness: 0.020" clear; rigid high density PVC

Sizes: Planks 6" x 36", Tiles 18" x 18" and 12" x 18"

Weight: 0.75 lb./sq. ft.

Weight/45 sf ctn: 33.75 lbs.

Edge Treatment: Square

Surface Texture: Standard as shown in sample folder

Test Performance

ASTM E 648 Critical Radiant Flux Class I CRF>0.45

ASTM E 662 Smoke Density Passes
ASTM F 925 Chemical Resistance Excellent

Slip Resistance Varies with surface texture

All ADA Compliant

FTC Slip Resistant Classified Product











High Performance LVT













SNT-205













