

Material Safety Data Sheet

Identification

Trade Name: Flex-Aire™ Cushion Modular
Product: Commercial Floor Covering

Hazard Identification

Hazardous Ingredients: None

Composition/Information on Ingredients

Product Class: Nylon faced floor covering with attached closed-cell thermoplastic cushion.

First-Aid Measures

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?
Health Hazards (Acute and Chronic): None Known
Medical Conditions Aggravated by Exposure: None Known.
Emergency First Aid Procedures: N/A

Fire-fighting Measures

Meets NFPA: Class 1
Flammable Limits: Non-flammable
Flash Point: Does not flash (ASTM-D 1929-77).
Extinguishing Media: Water or other Class A extinguishing agent.
Special Fire Fighting Procedures: None. Use same precautions required by a wood or paper type fire.

Accidental Release Measures

Steps to be taken in case material is released or spilled:
N/A

Handling and Storage

Keep dry - Store indoors for 72 hours prior to installation between 60°- 85° F and below 65% RH.
Other precautions: N/A

Exposure Controls/Personal Protection

This section refers to the above-mentioned Tandus product only. If additional installation products are used, always refer to the MSDS for all applicable installation products.
Ventilation Local Exhaust: Not required.
Protective Gloves: Not required.
Eye Protection: Not required.
Mechanical (General): Not required.
Work/Hygienic Practices: N/A.
Respiratory Protection: Not required.
Other Protective Clothing or Equipment: None.

Physical and Chemical Properties

Boiling Point: N/A Specific Gravity (water=1): >1
Vapor Pressure: N/A Melting Point: Above 212° F
Vapor Density: (Air=1) N/A
Evaporation Rate: N/A
Volatile Volume: N/A Water Volume: N/A
Solubility in Water: None
V.O.C.s: Meets the criteria defined by California's 01350 protocol, the Carpet and Rug Institute's Green Label Plus program and the Collaborative for High Performance Schools.



Flex-Aire™ Cushion Modular

Date Prepared: 8/17/2009

Tandus Flooring
1000 Vista Drive
Dalton, GA 30721

Emergency Telephone: 800-424-9300

Information Telephone: 800-241-4902

International Emergency: Call (USA) 202-483-7616



Stability and Reactivity

Stability: Stable.
Incompatibility: N/A.
Hazardous Polymerization: Will not occur.

Toxicological Information

Not available

Ecological Information

Not available

Disposal Considerations

Dispose of in accordance with Federal, State and Local regulations.
Tandus Flooring structured back products are 100% recyclable.
Recycle through Tandus Flooring FLOORE carpet reclamation program.

Transport Information

D.O.T Hazard Class: None
Placard Required: None

Regulatory Information

All components are in compliance with the inventory listing requirements of the U.S TSCA Inventory. This product does not contain asbestos.

Other Information

Tandus Flooring believes the data set forth herein are accurate as of the date hereof. Tandus Flooring makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.